



Product Information

Model	CM1510
Description	15" CRT monitor with Elo's breakthrough surface wave touch technology - iTouch "Touch on Tube"

Functional Features

Touch Screen	Technology	Elo iTouch (Surface Accoustic Wave)
	Interface	Serial or USB
	Surface Treatment	Anti-reflective, Anti-static
CRT	Type	FST CRT
	Size	15" Viewable Area
	Pixel Pitch	0.28 mm
Resolution	Max.	800 x 600 @ 85 Hz
	Recommended Preset	<ul style="list-style-type: none"> • 800 x 600 @ 85 Hz (VESA) • 640 x 480 @ 60 Hz (VGA)
Scanning Frequency	Horizontal	30~55 kHz
	Vertical	50~160 Hz
Video Input	Signal	Analog
	Connector	Mini D-Sub 15-Pin (female)
Video Function		Multi-lingual remote on-screen display (OSD), Built-in power, deflection/video test, Video diagnostic pin

Physical Features

Power Input		100~240 VAC, 50~60 Hz
Power Consumption	Max.	65 Watt
	Typical	55 Watt
Operating Conditions	Temperature	5°C~55°C
	Humidity	10%~80%
Storage Conditions	Temperature	-40°C~65°C
	Humidity	10%~90%
Regulations		FCC/ICES-03: Class B, UL/cUL (*Recognized component), TÜV-Bauart, CE, VCCI, C-tick, MPR II, DHHS, TCO99
Color		Beige or Dark Gray
Dimension		13.5" x 12.3" x 14.8"
Weight	Net	28 lbs
	Gross	33 lbs
Limited Warranty		2 years